


SAFETY MONITORING WARNING & CONTROL SYSTEMS



**MONITORS
CAMERA
CAMERA SYSTEM SUPPORT**



Part No./ Description
962016
5" TFT LCD Monitor

3 Camera Inputs, Both manually or automatically selectable
 Wired Trigger for each camera
 Anti-Glare Coating On Screen
 Electronic Distance Markings
 On-Screen Display (OSD)



Part No./ Description
962017

5.6" colour TFT LCD Screen
 1000G mechanical shock
 4G mechanical vibration
 12VDC (from control module)
 Camera selector (Up to 3 cameras)
 NTSC & PAL compatible
 12 watts (max) power consumption

CAMERA



Part No./ Description
962018
High Resolution 1/3" Sony CCD

Infra-Red LED for Ultra-Low Light Performance
 Rugged Lightweight Die-cast Aluminum Body
 Ip68 Dust/Waterproof Rating
 130° Viewing Angle
 Integral Microphone
 Adjustable Mounting Angle
 Corrosion Resistant



Part No./ Description
962019
Automatic Shutter with Overload Protection High Resolution 1/3" Sony CCD

Infra-Red LED for Ultra-Low Light Performance
 Rugged Lightweight Die-cast Aluminum Body
 Ip68 Dust/Waterproof Rating
 130° Viewing Angle
 Integral Microphone
 Adjustable Mounting Angle
 Corrosion Resistant
 Automatic Heating When the Temperature is Below 10° C



Part No./ Description
962021
High Resolution 1/4" Sony CCD

Ultra Compact Camera
 Automatic Electronic Iris
 Ip68 Dust/Waterproof Rating
 Adjustable Mounting Angle
 150° Extra Wide Field of View



Part No./ Description
962022
1/3" Super HAD Colour CCD

Electronic Auto Iris Control
 Auto White Balance (AWB)
 Back light Compensation
 Low illumination
 Ip68 Dust/Waterproof Rating
 125° Viewing Angle



Part No./ Description
962023
High Resolution 1/3" Sharp CCD

18 Iris RED LEDs for Ultra-Low Light Performance
 Electronic Auto Iris Control
 Auto White Balance (AWB)
 Back light Compensation
 Ip67 Dust/Waterproof
 110° Viewing Angle




Part No./ Description
962024
Split, Triple, or Quad Screen Splitter Box

4 Camera + AV Input
 Wired Triggers for All Camera
 Split Screen Trigger
 Timed Sequencing Option



Part No./ Description
962025
Value Bumper Camera

9 LEDs for ultra-low light performance
 8m illumination distance
 Mirror view
 1/3" Sharp CCD
 TV System: PAL
 TV Lines: 420



SAFETY MONITORING WARNING & CONTROL SYSTEMS

