

SAFETY MONITORING WARNING & CONTROL SYSTEMS



**MONITORS
CAMERA
CAMERA SYSTEM SUPPORT**



Part No./ Description
962016
5" TFT LCD Monitor

3 Camera Inputs, Both manually or automatically selectable
 Wired Trigger for each camera
 Anti-Glare Coating On Screen
 Electronic Distance Markings
 On-Screen Display (OSD)



Part No./ Description
962017

5.6: colour TFT LCD Screen
 1000G mechanical shock
 4G mechanical vibration
 12VDC (from control module)
 Camera selector (Up to 3 cameras)
 NTSC & PAL compatible
 12 watts (max) power consumption

CAMERA



Part No./ Description
962018
High Resolution 1/3" Sony CCD

Infra-Red LED for Ultra-Low Light Performance
 Rugged Lightweight Die-cast Aluminum Body
 Ip68 Dust/Waterproof Rating
 130° Viewing Angle
 Integral Microphone
 Adjustable Mounting Angle
 Corrosion Resistant



Part No./ Description
962019
Automatic Shutter with Overload Protection High Resolution 1/3" Sony CCD

Infra-Red LED for Ultra-Low Light Performance
 Rugged Lightweight Die-cast Aluminum Body
 Ip68 Dust/Waterproof Rating
 130° Viewing Angle
 Integral Microphone
 Adjustable Mounting Angle
 Corrosion Resistant
 Automatic Heating When the Temperature is Below 10° C



Part No./ Description
962021
High Resolution 1/4" Sony CCD

Ultra Compact Camera
 Automatic Electronic Iris
 Ip68 Dust/Waterproof Rating
 Adjustable Mounting Angle
 150° Extra Wide Field of View

**Part No./ Description****962022**
1/3" Super HAD Colour CCD

Electronic Auto Iris Control
Auto White Balance (AWB)
Back light Compensation
Low illumination
Ip68 Dust/Waterproof Rating
125° Viewing Angle

**Part No./ Description****962023**
High Resolution 1/3" Sharp CCD

18 Iris RED LEDs for Ultra-Low Light Performance
Electronic Auto Iris Control
Auto White Balance (AWB)
Back light Compensation
Ip67 Dust/Waterproof
110° Viewing Angle

**Part No./ Description****962024**
Split, Triple, or Quad Screen Splitter Box

4 Camera + AV Input
Wired Triggers for All Camera
Split Screen Trigger
Timed Sequencing Option

**Part No./ Description****962025**
Value Bumper Camera

9 LEDs for ultra-low light performance
8m illumination distance
Mirror view
1/3" Sharp CCD
TV System: PAL
TV Lines: 420

**Part No./ Description****962027****Composite Video and Stereo Audio Outputs**

Buckle Connection: 45cm

Buckle Connection type: Stalk/cable.

Webbing length: retractor to end bracket 291 cm

Retractor angle: Vertical

Complete with metal cover to protect the retractor

Aguide runner is provided to keep the webbing in position and reduce friction